



Material Safety Data Sheet



Beeswax white

Section 1. Chemical product and company identification

Manufacturer : HG International b.v. **Code** : 2800500
Address : Damsluisweg 70 1332 EJ Almere **MSDS#** : 1.02
Country : Netherlands **Validation date** : 5/19/2010.
Telephone No.: : +31 (0)36 54 94 700 **Print date** : 5/19/2010.
Fax : +31 (0)36 54 94 744 **Responsible name** : P. Stienstra
Internet: : www.hg.eu **Telephone No.:** : +1.705.726.5445
Supplier : Solstrand Trading **Fax** : +1.705.734.0857
Address : 60 Lockhart road Barrie, Ontario L4N 9G8 **Country** : Canada
Material uses : Consumer product.
In Case of Emergency : Chem. Tel Inc. (813) 248 0585 or Toll free (800) 255 3924

Section 2. Composition, Information on Ingredients

Name	CAS #	% by weight	Exposure limits
Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1	30 - 100	

Section 3. Hazards identification

Physical State and Appearance : Liquid.

Emergency overview : WARNING !
FLAMMABLE LIQUID AND VAPOR. COMBUSTIBLE.
Flammable liquid. Keep away from heat, sparks and flame. Avoid breathing vapor or mist. Avoid contact with skin and clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use.

Routes of entry : Dermal contact. Eye contact. Ingestion.

Potential acute health effects

Eyes : May cause eye irritation.
Skin : May cause skin irritation.
Inhalation : No known significant effects or critical hazards.
Ingestion : No known significant effects or critical hazards.

Potential chronic health effects : **CARCINOGENIC EFFECTS:** Not available.
MUTAGENIC EFFECTS: Not available.
TERATOGENIC EFFECTS: Not available.

Medical conditions aggravated by overexposure: : None known.

Over-exposure signs/symptoms : Not available.

[See toxicological information \(section 11\)](#)

Continued on next page

Section 4. First aid measures

- Eye Contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
- Skin Contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Inhalation** : Move exposed person to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Move exposed person to fresh air. Keep person warm and at rest. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Notes to Physician** : Not available.

Section 5. Fire fighting measures

- Flammability of the product** : May be combustible at high temperature.
- Auto-ignition Temperature** : 210°C (410°F)
- Flash Points** : Closed cup: 40°C (104°F). (Pensky-Martens.)
- Flammable limits** : Lower: 0.6% Upper: 6.5%
- Products of combustion** : Not available.
- Fire hazards in presence of various substances** : Not available.
- Explosion hazards in presence of various substances** : Not available.
- Fire fighting media and instructions** : In case of fire, use water spray (fog), foam, dry chemical or CO₂.
Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Flammable liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
- Special remarks on fire hazards** : Not available.
- Special remarks on explosion hazards** : Not available.

Section 6. Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Continued on next page

Methods for cleaning up : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

Section 7. Handling and storage

Handling : Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure Controls, Personal Protection

Engineering controls : Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits.

Personal protection

Eyes : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Skin : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Hands : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Other protection : Not available.

Personal protective equipment (Pictograms) :



Personal protection in case of a large spill : Splash goggles. Full suit. Boots. Gloves. Suggested protective clothing might not be adequate. Consult a specialist before handling this product.

Consult local authorities for acceptable exposure limits.

Section 9. Physical and chemical properties

Physical State and Appearance : Liquid.

Color : White.

Odor : Solvent.

pH : Not applicable.

Relative density : 0.78 g/cm³ (20°C / 68°F)

Continued on next page

Viscosity	: Dynamic: 100 cP
Solubility	: Partially soluble in the following materials: diethyl ether. Insoluble in the following materials: cold water, hot water.
Flash point	: Closed cup: 40°C (104°F). (Pensky-Martens.)
Explosive properties	: Not available.
Explosion Limits	: Lower: 0.6% Upper: 6.5%
Oxidizing properties	: Not available.
Physical chemical comments	: Not available.

Section 10. Stability and reactivity

Stability and Reactivity	: The product is stable.
Conditions of instability	: Keep from any possible contact with water.
Incompatibility with various substances	: Extremely reactive or incompatible with oxidizing agents, acids.
Hazardous Decomposition Products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hazardous polymerization	: Will not occur.

Section 11. Toxicological information

Chronic effects on humans	: Not available.
Other toxic effects on humans	: Slightly hazardous by the following route of exposure: of inhalation.
Special remarks on toxicity to animals	: Not available.
Special remarks on chronic effects on humans	: Not available.
Special remarks on other toxic effects on humans	: Not available.
Specific effects	
Carcinogenic effects	: No known significant effects or critical hazards.
Mutagenic effects	: No known significant effects or critical hazards.
Reproduction toxicity	: No known significant effects or critical hazards.

Section 12. Ecological information

Naphtha (petroleum), hydrodesulfurized heavy	Trout (LC50)	96 hour(s)	41.4 mg/l
	Shrimp. (IC50)	96 hour(s)	4.3 mg/l
BOD and COD	: Not available.		
Biodegradable/OECD	: Not available.		
Mobility	: Not available.		
Products of degradation	: Not available.		
Toxicity of the products of biodegradation	: Not available.		
Special remarks on the products of biodegradation	: Not available.		







Section 13. Disposal considerations

Waste information : The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Waste stream : Not available.

[Consult your local or regional authorities.](#)

Section 14. Transport information

Regulatory Information	UN number	Proper shipping name	Class	Packing group	Label	Additional information
DOT Classification	1300	"dangerous goods in limited quantities of class 3" UN 1300, PG III (Naphtha (petroleum), hydrodesulfurized heavy). Marine pollutant	3	III		Marine pollutant Severe marine pollutant (PP) Limited quantity Yes. Remarks Limited quantity for 500 ml package
TDG Classification	1300	"dangerous goods in limited quantities of class 3" UN 1300, PG III (Naphtha (petroleum), hydrodesulfurized heavy). Marine pollutant	3	III		Marine pollutant Marine pollutant (P) Remarks Limited quantity for 500 ml package
ADR/RID Class	1300	UN 1300, "dangerous goods in limited quantities of class 3", III, ADR (Naphtha (petroleum), hydrodesulfurized heavy)	3	III		Reportable quantity 45 Remarks Dangerous goods in limited quantities
IMDG Class	1300	"dangerous goods in limited quantities of class 3" UN 1300, PG III, (Naphtha (petroleum), hydrodesulfurized heavy). Marine pollutant (Naphtha (petroleum), hydrodesulfurized heavy)	3	III	 	Emergency schedules (EmS) 3-07 Marine pollutant Marine pollutant (P) Reportable quantity 30 Remarks Dangerous goods in limited quantities
IATA-DGR Class	1300	"dangerous goods in limited quantities of class 3" UN 1300, PG III, (Naphtha (petroleum), hydrodesulfurized heavy)	3	III		-

Continued on next page

Section 15. Regulatory information

WHMIS (Canada) : Class B-2: Flammable liquid
CEPA Toxic substances: None of the components are listed.
Canadian ARET: None of the components are listed.
Canadian NPRI: None of the components are listed.
Alberta Designated Substances: None of the components are listed.
Ontario Designated Substances: None of the components are listed.
Quebec Designated Substances: None of the components are listed.

International regulations

EINECS :

DSCL (EEC) : R10- Flammable.
R66- Repeated exposure may cause skin dryness or cracking.
R67- Vapors may cause drowsiness and dizziness.
R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

International lists : **Australia inventory (AICS):** Not determined.
China inventory (IECSC): Not determined.
Korea inventory (KECI): Not determined.
Philippines inventory (PICCS): Not determined.
Japan inventory (ENCS): Not determined.

Section 16. Other information

Label Requirements : FLAMMABLE LIQUID AND VAPOR. COMBUSTIBLE.

Hazardous Material Information System (U.S.A.)

Health	1
Fire hazard	2
Reactivity	0
Personal protection	

National Fire Protection Association (U.S.A.)



References : Not available.

Other special considerations : Not available.

Date of printing : 5/19/2010.

Date of issue : 5/19/2010.

Date of previous issue : No previous validation.

Version : 1.02

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.