



Material Safety Data Sheet



Stain away tie cleaner

Section 1. Chemical product and company identification

Manufacturer : HG International b.v. **Code** : 4380500
Address : Damsluisweg 70 1332 EJ Almere **MSDS#** : 1.02
Country : Netherlands **Validation date** : 3/17/2009.
Telephone No.: : +31 (0)36 54 94 700 **Print date** : 3/17/2009.
Fax : +31 (0)36 54 94 744 **Responsible name** : P. Stienstra
Internet: : www.hg.eu **Telephone No.:** : +1.705.726.5445
Supplier : Solstrand Trading **Fax** : +1.705.734.0857
Address : 60 Lockhart road Barrie, Ontario L4N 9G8 **Country** : Canada
Material uses : Cleaner.
In Case of Emergency : Chem. Tel Inc. (813) 248 0585 or Toll free (800) 255 3924

Section 2. Composition, Information on Ingredients

Name	CAS #	% by weight	Exposure limits
Naphtha (petroleum), hydrotreated light	64742-49-0	30 - 100	Not available.
Xylene	1330-20-7	5 - 15	Not available.
Perfume		0 - 1	Not available.
poly(oxy-1,2-ethanediyl), .alpha.,.alpha.'-[(9-octadecenylimino)di-2,1-ethanediyl]bis[.omega.-hydroxy-, (z)-	26635-93-8	0 - 1	Not available.

Section 3. Hazards identification

Physical State and Appearance : Liquid.

Emergency overview : DANGER
FLAMMABLE.
May cause fire.
Do not smoke.
Use only in well-ventilated areas.
Keep away from heat, sparks and flame.

Routes of entry : Dermal contact. Eye contact. Ingestion.

Potential acute health effects
Eyes : May cause eye irritation.
Skin : Harmful in contact with skin.
Inhalation : Can cause irritation.
Ingestion : Can cause irritation.

Potential chronic health effects : **CARCINOGENIC EFFECTS**: Classified A4 (Not classifiable for human or animal.) by ACGIH, 3 (Not classifiable for human.) by IARC [Xylene]. Classified 3 (Not classifiable for human.) by IARC [(R)-p-Mentha-1,8-diene].
MUTAGENIC EFFECTS: Not available.
TERATOGENIC EFFECTS: Not available.

Medical conditions aggravated by overexposure: : Repeated or prolonged exposure is not known to aggravate medical condition.

Continued on next page

Over-exposure signs/symptoms : Not available.

[See toxicological Information \(section 11\)](#)

Section 4. First aid measures

- Eye Contact** : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation occurs.
- Skin Contact** : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention.
- Inhalation** : If inhaled, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.
- Ingestion** : Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention if symptoms appear.
- Notes to Physician** : Not available.

Section 5. Fire fighting measures

- Flammability of the product** : Flammable.
- Auto-ignition Temperature** : 210°C (410°F)
- Flash Points** : Closed cup: Between -18°C (0°F) and 23°C (73°F). (Pensky-Martens.)
- Flammable limits** : Lower: 0.6% Upper: 6.5%
- Products of combustion** : Decomposition products may include the following materials: carbon oxides (CO, CO₂).
- Fire hazards in presence of various substances** : Highly flammable in presence of heat.
- Explosion hazards in presence of various substances** : Not available.
- Fire fighting media and instructions** : In case of fire, use water spray (fog), foam, dry chemicals, or CO₂.
Flammable liquid and vapor. Vapor may cause flash fire. Vapors may accumulate in low or confined areas, travel considerable distance to source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.
- Special protective equipment for fire-fighters** : Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full facepiece operated in positive pressure mode.
- Special remarks on fire hazards** : Not available.
- Special remarks on explosion hazards** : Not available.

Section 6. Accidental release measures

- Personal precautions** : Immediately contact emergency personnel. Eliminate all ignition sources. Keep unnecessary personnel away. Use suitable protective equipment (Section 8). Do not touch or walk through spilled material.
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- Methods for cleaning up** : If emergency personnel are unavailable, contain spilled material. For small spills add absorbent (soil may be used in the absence of other suitable materials) and use a non-sparking or explosion proof means to transfer material to a sealed, appropriate container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.

Section 7. Handling and storage

- Handling** : Avoid prolonged contact with eyes, skin, and clothing. Keep container closed. Use only with adequate ventilation. Keep away from heat, sparks and flame. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Wash thoroughly after handling.
- Storage** : Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).

Continued on next page

Section 8. Exposure Controls, Personal Protection

Engineering controls : Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are proximal to the work-station location.

Personal protection

Eyes : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
Recommended:safety glasses with side shields

Skin : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Body: Recommended:Work uniform or laboratory coat.

Respiratory : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Recommended:Ventilation is normally required when handling or using this product.

Hands : Chemical-resistant, impervious gloves or gauntlets complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
>8 hour(s) (breakthrough time): polyvinyl alcohol (PVA)

Other protection : Not available.

Personal protective equipment (Pictograms) :



Personal protection in case of a large spill : Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self-contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

[Consult local authorities for acceptable exposure limits.](#)

Section 9. Physical and chemical properties

Physical State and Appearance : Liquid.

Color : Colorless.

Odor : Characteristic.

pH : Not applicable.

Relative density : 0.725 g/cm³ (20°C / 68°F)

Viscosity : Not available.

Solubility : Insoluble in the following materials: cold water, hot water.

Flash point : Closed cup: Between -18°C (0°F) and 23°C (73°F). (Pensky-Martens.)

Flammability (solid, gas) : Not applicable.

Explosive properties : Not available.

Explosion Limits : Lower: 0.6% Upper: 6.5%

Oxidizing properties : Not applicable

Physical chemical comments : Not available.

Section 10. Stability and reactivity

Stability and Reactivity : The product is stable.

Conditions of instability : Keep away from heat, sparks and flame. Stable under recommended storage and handling conditions (see section 7).

Incompatibility with various substances : Not available.

Hazardous Decomposition Products : Not available.

Hazardous polymerization : Will not occur.

Continued on next page

Section 11. Toxicological information

Xylene	LD50	4300 mg/kg	Oral	Rat
	LD50	2119 mg/kg	Oral	Mouse
	LD50	4300 mg/kg	Oral	Mammal
	LD50	>1700 mg/kg	Dermal	Rabbit
	LD50	1700 mg/kg	Dermal	Rabbit
	LDLo	50 mg/kg	Oral	human

Chronic effects on humans : **CARCINOGENIC EFFECTS:** Classified A4 (Not classifiable for human or animal.) by ACGIH, 3 (Not classifiable for human.) by IARC [Xylene]. Classified 3 (Not classifiable for human.) by IARC [(R)-p-Mentha-1,8-diene].

Contains material which causes damage to the following organs: blood, kidneys, liver, gastrointestinal tract, skin, central nervous system (CNS), eye, lens or cornea.

Other toxic effects on humans : Extremely hazardous by the following route of exposure: of inhalation (lung irritant).
Hazardous by the following route of exposure: of skin contact (irritant).

Special remarks on toxicity to animals : Not available.

Special remarks on chronic effects on humans : Not available.

Special remarks on other toxic effects on humans : Not available.

Specific effects

Carcinogenic effects : Contains material which may cause cancer based on animal data. Risk of cancer depends on duration and level of exposure.

Mutagenic effects : No known significant effects or critical hazards.

Reproduction toxicity : No known significant effects or critical hazards.

Section 12. Ecological information

Xylene	Oncorhynchus mykiss (LC50)	96 hour(s)	3.3 mg/l
	Oncorhynchus mykiss (LC50)	96 hour(s)	8.2 mg/l
	Lepomis macrochirus (LC50)	96 hour(s)	8.6 mg/l
	Lepomis macrochirus (LC50)	96 hour(s)	12 mg/l
	Lepomis macrochirus (LC50)	96 hour(s)	13.3 mg/l
	Pimephales promelas (LC50)	96 hour(s)	13.4 mg/l

BOD and COD : Not available.

Biodegradable/OECD : Not available.

Mobility : Not available.

Products of degradation : Decomposition products may include the following materials: carbon oxides (CO, CO₂) and water.

Toxicity of the products of biodegradation : The products of degradation are less toxic than the product itself.

Special remarks on the products of biodegradation : Not available.

Section 13. Disposal considerations






Waste information : The generation of waste should be avoided or minimised wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Waste stream : Not available.

Consult your local or regional authorities.

Continued on next page

Section 14. Transport information

Regulatory Information	UN number	Proper shipping name	Class	Packing group	Label	Additional information
DOT Classification	3295	"dangerous goods in limited quantities of class 3" UN 3295, PG II (Naphtha (petroleum), hydrotreated light). Marine pollutant	3	II		Marine pollutant Marine pollutant (P) Limited quantity Yes. Remarks Limited Quantity
TDG Classification	3295	"dangerous goods in limited quantities of class 3" UN 3295, PG II (Naphtha (petroleum), hydrotreated light). Marine pollutant	3	II		Marine pollutant Marine pollutant (P) Remarks Limited Quantity
ADR/RID Class	3295	UN 3295, "dangerous goods in limited quantities of class 3", II, ADR (Naphtha (petroleum), hydrotreated light)	3	II		Hazard identification number 33 Reportable quantity 12 Remarks Marine pollutant Dangerous goods in limited quantities
IMDG Class	3295	"dangerous goods in limited quantities of class 3" UN 3295, PG II (Naphtha (petroleum), hydrotreated light). Marine pollutant (poly(oxy-1,2-ethanediyl), .alpha.,.alpha.'-[(9-octadecenyylimino)di-2,1-ethanediyl]bis[.omega.-hydroxy-, (z)-)	3	II		Emergency schedules (EmS) F-E, S-D Marine pollutant Marine pollutant (P) Remarks Dangerous goods in limited quantities
IATA-DGR Class	3295	"dangerous goods in limited quantities of class 3" UN 3295, PG II (Naphtha (petroleum), hydrotreated light)	3	II		Remarks Marine pollutant

Section 15. Regulatory information

WHMIS (Canada) : Class B-2: Flammable liquid with a flash point lower than 37.8°C (100°F).
No products were found.

International regulations

EINECS : Not available.

DSCL (EEC) : R11- Highly flammable.
R20/21- Harmful by inhalation and in contact with skin.
R65- Harmful: may cause lung damage if swallowed.

International lists :

Continued on next page

Section 16. Other information

Label Requirements : FLAMMABLE.
May cause fire.

Hazardous Material Information System (U.S.A.)

Health	*	2
Fire hazard		4
Reactivity		0
Personal protection		B

National Fire Protection Association (U.S.A.)



References : Not available.

Other special considerations : Not available.

Date of printing : 3/17/2009.

Date of issue : 3/17/2009.

Date of previous issue : No previous validation.

Version : 2

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.